

**BOLO PROJECT- 2009 DRILL ASSAYS**

DH	Gold Values					Silver Values					T.D. (ft)	Dip	Direction	Area
	Interval	Thickness	Au	Thickness	Au	Interval	Thickness	Ag	Thickness	Ag				
	(Ftg)	(ft)	(opt)	(m)	(ppm)	(Ftg)	(ft)	(opt)	(m)	(ppm)				
BL-29	155-360	205	0.019	62.5	0.647						500	-45	N90W	Mine Fault Zone
incl	165-180	15	0.050	4.6	1.717									
						235-360	125	0.79	38.1	27.0				
	255-265	10	0.099	3.0	3.409	incl 285-300	15	3.10	4.6	106.4				
	395-400	5	0.025	1.5	0.840									
BL-30	355-410	55	0.006	16.8	anom	405-410	5	0.29	1.5	10.0	600	-45	N65W	Mine Fault Zone
BL-31	360-375	15	0.030	4.6	1.025	380-385	5	0.34	1.5	11.7	600	-45	S50W	Mine Fault Zone
BL-32	185-220	35	0.003	10.7	anom						565	-45	N55W	Mine Fault Zone
	220-390	170	0.024	51.8	0.813									
incl	220-230	10	0.067	3.0	2.284									
	300-330	30	0.056	9.1	1.910									
						310-365	55	0.39	16.8	13.3				
	390-430	40	0.006	12.2	anom									
BL-33	230-235	5	0.005	1.5	anom					All < 10	800	-70	N90W	Mine Fault Zone
	380-400	20	0.007	6.1	anom									
BL-34	all < 100 ppb			0.0	< 0.100 ppm						925	-90	--	Wood Canyon